

Complete Multiple Tasks in One with Easy-to-read Color Touch Screen.

Pantum M7300 series makes your jobs easier with 3.5 inch color touch screen. It makes your work more efficient with multifunction in one, high print and copy speed and autoduplex printing and scanning meanwhile makes your outputs more affordable and ecofriendly with separate drum unit and toner cartridge. It aims to meet the requirements of small to large workgroups using satisfying function and outstanding performance.



MONO

Easy-to-read 3.5 inch color touch screen



One-step driver installation and direct printing



Office document direct print from mobile devices



Confidential **Printing**



Automatic Duplex Printing and Scanning



USB Disk Direct Printing



KEY SPECIFICATIONS

MODEL	■M7300FDN : ■M7300FDW
Print speed ⁽¹⁾	33ppm (A4) / 35ppm (Letter)
Time to First Page ⁽¹⁾	Soppin (44) / Soppin (Editor) ≤8.5s
	60000 Pages
Maximum Monthly Duty Cycle	Ţ
Recommended Monthly Page Volume	
Print Resolution	Max 1200x1200 dpi
Printer Languages	PCL5e, PCL6, PS, PDF
Processor Memory	600MHz
	512 MB
Duplex Printing	Auto
Control Panel	3.5 inch touch screen
USB Printing	Yes
Security Printing	Yes
Google Cloud Printing	Yes
NFC Connection	No Yes
PYING	
Copy Speed ⁽¹⁾	33cpm (A4) / 35cpm (Letter)
Time to First Copy ⁽¹⁾	Flatbed: Less than 10s / ADF: Less than 11s
Copy Resolution	Max 600 x 600dpi
Continuous Copy Page	1-99 Page(s)
Zoom	25%~400%
Additional Function	25%~400% ID copy, Receipt copy, N-up copy, Clone copy, Poster copy, Manual duplex copy, Collated copy
ANNING	то сору, теоспресору, те ир сору, стопте сору, тоздет сору, iviatrual duplex сору, contated copy
Scan Type	Flatbed+ADF
Duplex Scanning ⁽¹⁾	
	Yes, 24ppm (48ipm)
ADF Capacity	50 Pages
Scan Speed ⁽¹⁾ Max Scan Size	24 ppm (A4) / 25 ppm (Letter)
	Flatbed: 216 x 297mm ADF: 216 x 356 mm
Scan Resolution	Flatbed: Max 1200 x 1200dpi ADF: Max 600 x 600dpi
Color Scanning	Yes
Output Function	Scan to PC, Email, FTP, USB
XING Fax Type	Mono
Modem Max Speed	33.6Kbps
Fax Resolution	33.6Kops Max 300 x 300 dpi
Fax Memory	650 Pages
Coded System	MH / MR / MMR / JBIG
Compatibility(1)	ITU-T SG3/ECM
Fax Feature	PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, PC-FAX(only sending), DC-FAX(only sendin
PER HANDLING	Delayed Send, Auto Recive, Auto Reduction, Fax Forwarding, Quick-dual, Gloup Dial, PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dual, Gloup Dial, Pax Forwarding, Quick-dual, Gloup Dial, Pax Barrier, Multi-send, Fax Forwarding, Quick-dual, Gloup Dial, Pax Barrier, Multi-send, Gloup D
Paper Input Tray	250 Pages
Multipurpose Tray	1 Page
ADF Capacity	50 pages
Paper Output Capacity	
	150 pages (A4/70g)
Media Type	Plain, Thick, Thin, Transparency, Cardstock, Label, Envelope
Media Size	A4, A5, JIS B5, IS0 B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, Monarch Env, DL Env, C5 IC6 Env, No.10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2
Media Weight	Standard Tray: 60-105g/m² Multipurpose Tray: 60-200g/m²
NERAL	· / · · · · · · · · · · · · · · · · · ·
Product Dimension (wxdxh)	415 x 360 x 352mm
Weight (without toner cartridge	
Environment	Best Temperature: 10~32°C Relative Humidity: 20%~80%
Noise	Print: 52dB(A) Copy: 54dB(A) Scan: 52dB(A) Standby: 30dB(A)
Power Consumption	Print: Average 550W Standby: Less than 50W Dormant: Less than 2 W
Operating System	Microsoft Windows Server2003/Server2008/Server2012/XP/Vista/Win7/Win8/Win8.1/Win10(32/64 Bit); Mac OS 10.7-10.13; Linux: Ubuntu 12.04/14.04(32/64 Bit)
Mobile Operating system comp	patibility iOS 7.0 and above; Android 4.4 and above
Interface	High Speed USB 2.0 High Speed USB 2.0 Net: IEEE 802.3 10/100Base-Tx
IPPLIES	WiFi: IEEE 802.11b/g/n
Cartridge Type	Separate Drum and Toner
Starter Cartridge / Drum Unit ⁽²⁾	1500 Pages / 12000 Pages
	1500 Pages / 12000 Pages TL-410 (1500 pages), TL-410H (3000 pages), TL-410X (6000 pages)

⁽¹⁾ Up to (2) As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)

Copyright © 20 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein. *Printer data based on Pantum internal testing